


Miller 8815-12 and 8815-24 Shadow Beam Anchor

Materials

- Foot Ends**Aluminum
 - Support Shaft**.....Stainless Steel
 - Retractable Plunger**.... Stainless Steel
 - D- Ring Attachment**.....Plated, Drop forged steel and stainless steel
 - Hardware**.....Steel Minimum Tensile strength
- *All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Technical


- Max Working Load**:.....400 lbs (181.4 kg)
- Minimum Tensile Strength**.....5000 lbs. (22kN)
- Fits Flange Sizes**.....See Chart Below
- Weight**.....See Chart Below



Identification

- Label Materials**.....Lexan and Valeron
- Label Contents**..... Inspection, Type, Model, Date
Size, Material Specs,
Capacity, Certifications.

Miller Shadow Beam Anchors connect horizontally to a wide range of I and H beam flanges from 4 inches (100mm) to 24 inches (610mm) wide and up to 2-1/2 inches thick. The fixed unit (Model 8815) is designed to be tightened horizontally or vertically, firmly gripping the beam or column to provide a temporary or permanent anchorage attachment.



Model No.	Fits Flange Sizes	Weight
8815-12	4" to 12" (100mm to 305mm)	7.75lbs (3.1kg)
8815-24	12" to 24" (305mm to 610mm)	13.65lbs (6.19kg)



by Honeywell

Toll Free 800.873.5242 (press 4) • hsptechsupport@honeywell.com • www.millerfallprotection.com

▲ WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.