Miller StretchStop® Lanyards w/Shock Absorber

Description

Miller StretchStop Lanyards combine the integral SofStop® Shock Absorber with a unique stretchable lanyard design reducing tripping hazard.

Materials

Webbing:

• Safety Strap: Type 7 webbing

Safety Jacket: Green tubular polyester web

Thread: 6 cord bonded 3 strand

polyester

Hardware: Steel

* All hardware meets ASTM (50) fifty-hour salt spray test requirements.

SofStop Cover: Vinyl Label Materials: Valeron

Technical/Certification

Minimum Tensile strength

Webbing: 5,000 lbs. (22kN)
 Thread: 42 lbs. (0.19kN)
 Locking Snap Hooks: 5,000 lbs. (22kN)

3/4 in. (19mm) gate opening
• Locking Rebar Hooks: 2 ½ in. (63mm) gate opening

SofStop® Pack Max Working Load Capacity

OSHA/ANSI: 310 lbs (141 kg) CSA: 254 lbs. (115 kg)



Certification Product Category 1

OSHA 1926.502, 1910.66; ANSI A10.32 and CSA Z259.11

Elongation/Deceleration

Distance: 42 in. (107cm)
Fall Arrest Force: 900 lbs. max. (4kN)

Certification Product Category 2

ANSI Z359.13 (Applies to products with "Z7" in the model number)

Elongation/Deceleration

Distance: 48 in. (122cm)

Fall Arrest Force: 900 lbs. avg. (4kN) / 1,800 lbs.

max. (8kN)

Model		# Legs	Harness Connection	Anchorage Connection	Weight(s)	
StretchStop® Lanyards w/SofStop® Shock Absorbing Pack						
CATEGORY 1	CATEGORY 2				CATEGORY 1	CATEGORY 2
913SS	913SS-Z7	1	Locking snap hook	Locking snap hook	2.2 lbs (1kg)	2.3 lbs (1kg)
913RSS	913RSS-Z7	1	Locking snap hook	Locking rebar hook	3.0 lbs (1kg)	3.1 lbs (1kg)
8798SS	8798SS-Z7	2	Locking snap hook	Locking snap hooks	3.2 lbs (2kg)	3.3 lbs (2kg)
8798RSS	8798RSS-Z7	2	Locking snap hook	Locking rebar hooks	4.5 lbs (2kg)	4.6 lbs (2kg)

Standard length is 6 ft (1.8m). Models are available in lengths from 4 ft. (1.2m) to 10 ft. (3m).



by Honeywell

Toll Free 800.873.5242 (press 4) • hsptechsupport@honeywell.com • www.millerfallprotection.com