

## TECHNICAL DATA

SP399 Rev B/04-16

# Miller Titan™ II Tubular Shock-Absorbing Lanyards

## Description

Miller Titan™ II Tubular Shock-Absorbing Lanyards feature an outside jacket and a built-in woven inner core which smoothly expands, reducing fall arrest forces.

## Materials

### Webbing:

- Safety Strap: Polyester webbing
- Safety Jacket: Tubular polyester

**Thread:** Polyester

**Label:** Valeron

### Hardware:

Steel 5,000 lb. (22 kN)

\* All hardware meets ASTM (50) fifty-hour salt spray test requirements.

## Technical

- Locking Snap Hooks: 3/4 in. (19 mm) opening
- Locking Rebar Hooks: 2 1/2 in. (63 mm) opening
- Webbing: 5,000 lbs. (22 kN)

### Max. Weight Capacity:

**OSHA/ANSI:** 310 lbs. (141 kg)

**CSA:** 254 lbs. (115 kg)

### Elongation/Deceleration Distance:

**OSHA/ANSI:** 48 in. (122 cm)

**CSA:** 46 in. (117 cm)

### Peak Arresting Force:

**OSHA/ANSI:** 1,800 lbf. (8 kN)

**CSA:** 900 lbf. (4 kN)



T5111-Z7/6FTAFC

## Certification

Meets all OSHA 1926.502, ANSI A10.32, ANSI Z359.13, and CSA Z259.11-05, Class B and E4 requirements.

Connecting components meet or exceed ANSI Z359.12-2009 or CSA Z259.12-11 requirements for 3,600 lb. gate strength. For questions about products purchased prior to January 1, 2015, please contact Honeywell Technical Service at 800.873.5242.

| Model Number    | Canadian Model Number | Number of legs | Harness Connection | Anchorage Connection      | Lanyard Length |
|-----------------|-----------------------|----------------|--------------------|---------------------------|----------------|
| T5111-Z7/6FTAFC | T5111-Z7/6FTAFC       | One            | Locking Snap Hook  | Locking Snap Hook         | 6 ft. (1.8m)   |
| T5112-Z7/6FTAFC | T5112-Z7/6FTAFC       | One            | Locking Snap Hook  | Large Locking Rebar Hook  | 6 ft. (1.8m)   |
| T5113-Z7/6FTAFC | T5113-Z7/6FTAFC       | One            | Locking Snap Hook  | Small Locking Rebar Hook  | 6 ft. (1.8m)   |
| T5121-Z7/6FTAFC | T5121-Z/6C            | Two            | Locking Snap Hook  | Locking Snap Hooks        | 6 ft. (1.8m)   |
| T5122-Z7/6FTAFC | T5122-Z7/6FTAFC       | Two            | Locking Snap Hook  | Large Locking Rebar Hooks | 6 ft. (1.8m)   |
| T5123-Z7/6FTAFC | Not Available         | Two            | Locking Snap Hook  | Small Locking Rebar Hook  | 6 ft. (1.8m)   |

Available from 4 ft. (1.2 m) to 10 ft. (3 m) lengths.

**Limitless Possibilities. Ask the Expert.**

**Technical Service: 800.873.5242**

[www.millerfallprotection.com](http://www.millerfallprotection.com)

### Honeywell Industrial Safety

900 Douglas Pike  
Smithfield, RI 02917

### USA

Phone: 800.430.5490  
Fax: 800.322.1330

### Canada

Phone: 888.212.7233  
Fax: 888.667.8477

**⚠ WARNING!** This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.